

The Cutting Edge



Brief Description

Oil hydraulic heavy duty mini-shear with single or three phase electric motor. Bronze bearings throughout.

Features

- Four sided reversible serrated blades.
- Tank mounted motor.
- Four way fork-lift entry base.
- Tool kit included
- Supplied ready to work.
- Foot pedal control – single or automatic stroke.
- Compact with parts accessible for easy service.
- Adjustable blade opening.
- Fully adjustable head guard.
- Adjustable head bearings
- Adjustable blades.

Deltax reserves the right to alter the product specification in any way without giving prior notification.

Specification	Dimension	DTX 340
Overall	Length	1194mm (47")
	Width	760mm (30")
	Height	1205mm (47½")
	Weight	475kg
Blade	Length	340mm (13⅜")
	Opening	50 - 162mm (2" - 6⅜")
Blade Table	Height	794mm (31¼")
Max Shear Force	Tonnes Force	50
Shear Capacity	Steel Round Bar 45 kg/mm	30 (1 ⅜")
Oil	ISO 46	135ltr (30 Gall)
Horsepower	Single Phase	3HP (2.2kW)
	Three Phase	5.5HP (4kW)
Speed	Single Phase	7½ - 30 cuts/min
	Three Phase	15 - 60 cuts/min

Tel: +46 (0) 31 760 60 16
www.prominova.se

Fax: +46 (0) 31 31 33 376
info@prominova.se